

Specifications for PIXMA E560

Printer			
Maximum Printing Resolution	4800 (horizontal)* ¹ x 1200 (vertical) dpi		
Print Head / Ink	Type:	FINE Cartridge	
	Number of Nozzles:	Total 1,792 nozzles	
	Ink Droplet Size:	2pl	
	Ink Tank:	PG-89, CL-99	
Print Speed* ² Based on ISO / IEC 24734. Click here for summary report Click here for Document Print and Copy Speed Measurement Conditions	Document: Col	ESAT / Simplex	approx. 5.7ipm
	Document: B / W	ESAT / Simplex	approx. 9.9ipm
	Photo (4 x 6")	PP-201 / Borderless	approx. 44secs.
Printable Width	Up to 203.2mm (8inch), Borderless: Up to 216mm (8.5inch)		
Printable Area	Borderless Printing* ³	Top / Bottom / Right / Left margin: each 0mm (Supported Paper Size: A4, LTR, 4 x 6" ,5 x 7" ,8 x 10")	
	Bordered Printing	Top margin: 3mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (LTR / LGL: Left: 6.4mm, Right: 6.3mm)	
	Bordered Auto 2-sided printing	Top margin: 5mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (LTR / LGL: Left: 6.4mm, Right: 6.3mm)	
Recommended Printing Area	Top margin: 32.5mm / Bottom margin: 33.5mm		
Paper Size	A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", 8 x 10", Envelopes (DL, COM10), Custom size (width 89mm - 215.9mm, length 127mm - 676mm)		
Paper Handling - Front Tray (Maximum Number)	Plain Paper	A4, A5, B5, LTR=100, LGL=10	
	High Resolution Paper (HR-101N)	A4=80	
	Photo Paper Pro Platinum (PT-101)	4 x 6"=20, A4=10	
	Photo Paper Plus Glossy II (PP-201)	4 x 6"=20, A4=10	
	Photo Paper Pro Luster (LU-101)	A4=10	
	Photo Paper Plus Semi-Gloss (SG-201)	4 x 6"=20, A4, 8 x 10"=10	
	Glossy Photo Paper "Everyday Use" (GP-601)	4 x 6"=20, A4=10	
	Matte Photo Paper (MP-101)	4 x 6"=20, A4=10	
	Envelope	European DL / US Com. #10=5	
Support Media for Auto 2-sided printing	Type	Plain Paper	
	Size	A4, A5, B5, LTR	

Paper Weight	- Front Tray	Plain Paper: 64-105 g/m ² , Canon specialty paper: max paper weight: approx. 300 g/m ² (Photo Paper Pro Platinum PT-101)
Ink End Sensor	Dot count	
Print Head Alignment	Manual	
Scan * ⁴		
Scanner Type	Flatbed	
Scanning Method	CIS (Contact Image Sensor)	
Optical Resolution* ⁵	1200 x 2400dpi	
Selectable Resolution* ⁶	25 - 19200dpi	
Scanning Bit Depth (Input / Output)	Grayscale:	16bits / 8bits
	Colour:	48bits / 24bits (RGB each 16bits / 8bits)
Line Scanning Speed* ⁷	Grayscale:	1.2ms/line (300dpi)
	Colour:	3.5ms/line (300dpi)
Scanning Speed* ⁸	Reflective: A4 Colour / 300dpi	Approx. 14secs.
Maximum Document Size	Flatbed:	A4 / LTR (216 x 297mm)
Copy		
Maximum Document Size	A4 / LTR (216 x 297mm)	
Compatible Media	Size:	A4, LTR, 4 x 6" (PP-201)
	Type:	Plain Paper Photo Paper Plus Glossy II (PP-201) (4"×6")
Image Quality	Plain Paper:	Fast, Standard
Copy Speed* ⁹ Based on ISO / IEC 24735 and ISO / IEC 29183 standard. Click here for summary report Click here for Document Print and Copy Speed Measurement Conditions	Document: Colour: sFCOT / Simplex:	approx. 25secs.
	Document: Colour: sESAT / Simplex:	Approx. 2.5ipm
Multiple Copy	Black / Colour	1 - 21 pages
Network		
Protocol	TCP/IP	
Wireless LAN	Network Type	IEEE802.11n / IEEE802.11g / IEEE802.11b
	Frequency Band	2.4GHz
	Channel* ¹⁰	1-13
	Range	indoor 50m (depends on the transmission speed and conditions)
	Security	WEP64 / 128bit, WPA-PSK

		(TKIP/AES), WPA2-PSK (TKIP/AES)
System Requirements		
Windows:	(Please visit www.canon-asia.com to check OS compatibility and to download the latest driver updates.)	Windows 8 / Windows 7 / Windows XP / Windows Vista
Macintosh:		Mac OS X v10.6.8 and later
General Specifications		
Interface	Wireless LAN IEEE 802.11 b / g / n, USB 2.0 Hi-Speed	
Google Cloud Print	Available	
PIXMA Printing Solutions	Available	
Operating Environment	Temperature: 15 - 30°C; Humidity: 10 - 80% RH (no dew condensation)	
Storage Environment	Temperature: 0 - 40°C; Humidity: 5 - 95% RH (no dew condensation)	
Acoustic Noise (PC Print)	Photo (4" x 6")* ¹¹	approx. 42.5dB(A)
Power	AC 100 - 240V, 50 / 60Hz	
Power Consumption	Standby (scanning lamp is off) Wireless LAN connection to PC	Approx. 1.7W
	OFF:	Approx. 0.3W
	Copying* ¹² Wireless LAN connection to PC	Approx. 16W
Environment	Regulation:	RoHS (EU, China), WEEE (EU)
	Eco-Label:	Energy Star
Dimension (W x D x H)		approx. 449 x 304 x 152mm
Weight		approx. 5.4kg