

Specifications for PIXMA MG2570S

Print		
Maximum Printing Resolution	4800 (horizontal)* ¹ x 600 (vertical)dpi	
Print Head / Ink	Type:	FINE Cartridge
	Number of Nozzles:	Total 1,280 nozzles
	Ink Droplet Size (minimum):	2pl
	Ink Cartridge:	PG-745S, CL-746S (PG-745, CL-746, PG-745XL, CL-746XL – Optional)
Print Speed Based on ISO / IEC 24734. Click here for summary report Click here for Document Print and Copy Speed Measurement Conditions	Document: Colour* ² : ESAT / Simplex:	Approx. 4.0ipm
	Document: B/W* ² : ESAT / Simplex:	Approx. 8.0ipm
Printable Width	Up to 203.2 mm (8 inch)	
	Bordered Printing:	Top margin: 3mm, Bottom margin: 16.7mm, Left / Right margin: each 3.4mm (LTR / LGL: Left: 6.4mm, Right: 6.3mm)
Recommended Printing Area	Top Margin:	31.6mm
	Bottom Margin:	29.2 mm
Paper Size	A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", Envelopes (DL, COM10), Custum size (width 101.6mm - 215.9mm, length 152.4mm - 676mm)	
Paper Handling (Rear Tray) (Maximum Number)	Plain Paper	A4, A5, B5, LTR = 60, LGL = 10
	Photo Paper Plus Glossy II (PP-201)	4 x 6" = 20
	Glossy Photo Paper "Everyday Use" (GP-501) Glossy Photo Paper "Everyday Use" (GP-601)	4 x 6" = 20
	Envelope	European DL / US Com. #10 = 5
Paper Weight	Cassette:	Plain Paper: 64 - 105 g/m ² , Canon specialty paper: max paper weight: approx. 275 g/m ² (Photo Paper Plus Glossy II (PP-201)
Ink End Sensor	Dot count	
Print Head Alignment	Manual	
Scan * ⁴		
Scanner Type	Flatbed	
Scanning Method	CIS (Contact Image Sensor)	
Optical Resolution* ⁵	600 x 1200dpi	

Selectable Resolution* ⁶	25 - 19200dpi	
Scanning Bit Depth (Input / Output)	Grayscale:	16 bits / 8 bits
	Colour:	48 bits / 24 bits (RGB each 16 bits / 8 bits)
Line Scanning Speed* ⁷	Grayscale:	1.2 ms/line (300dpi)
	Colour:	3.5 ms/line (300dpi)
Scanning Speed* ⁸	Reflective: A4 Colour / 300dpi	Approx. 14secs.
Maximum Document Size	Flatbed:	A4 / LTR (216 x 297mm)
Copy*⁹		
Maximum Document Size	A4 / LTR (216 x 297mm)	
Compatible Media	Size:	A4, LTR
	Type:	Plain Paper
Image Quality	Plain Paper:	Fast, Standard
Copy Speed* ¹⁰ Based on ISO / IEC 29183. Click here for summary report Click here for Document Print and Copy Speed Measurement Conditions	Document: Colour: sFCOT / Simplex:	Approx. 31secs.
	Document: Colour: sESAT / Simplex:	Approx. 1.6ipm
Multiple Copy	Black / Colour	1 - 21 pages
System Requirements (Please visit www.canon-asia.com to check OS compatibility and to download the latest driver updates.)	Windows:	Windows 8 / Windows 7 / Window Vista / Windows XP
	Macintosh:	Mac OS X v10.7.5 and later
General		
Interface	USB 2.0 Hi-Speed	
Operating Environment	Temperature:	5 - 35°C
	Humidity:	10 - 90% RH (no dew condensation)
Storage Environment	Temperature:	0 - 40°C
	Humidity:	5 - 95% RH (no dew condensation)
Power	AC 100 - 240V, 50 / 60Hz	
Power Consumption	Standby (scanning lamp is off) (USB connection to PC):	Approx. 1.0W
	OFF:	Approx. 0.4W
	Copying* ¹¹ : (USB connection to PC)	Approx. 9W
Environment	Regulation:	RoHS (EU, China), WEEE (EU)
	Eco-Label:	Energy Star, EPEAT
Dimension (W x D x H)	Approx. 426 x 306 x 145mm	
Weight	Approx. 3.5kg	