

Specifications for PIXMA iP7270

Print		
Maximum Printing Resolution	9600 (horizontal)* ¹ x 2400 (vertical)dpi	
Print Head / Ink	Type:	Individual Ink Cartridges
	Total Number of Nozzles:	5,120 nozzles
	Min. Ink Droplet Size:	1pl
	Ink Tank:	PGI-750 Pigment Black, CLI-751 Cyan / Magenta / Yellow / Black (Optional: PGI-750XL Pigment Black, CLI-751XL Cyan / Magenta / Yellow / Black)
Print Speed Based on ISO / IEC 24734. Click here for summary report Click here for Document Print and Copy Speed Measurement Conditions	Document: Colour* ² : ESAT / Simplex:	Approx. 10.0ipm
	Document: B/W* ² : ESAT / Simplex:	Approx. 15.0ipm
	Photo (4 x 6")* ² : PP-201 / Borderless:	Approx. 21secs.
Printable Width	Up to 203.2mm (8-inch)	
	Borderless:	Up to 216mm (8.5-inch)
Printable Area	Borderless Printing* ³ :	Top / Bottom / Right / Left margin: each 0mm (Supported Paper Size: A4 / LTR / 4 x 6" / 5 x 7" / 8 x 10")
	Bordered Printing:	Top margin: 3mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (LTR / LGL: Left: 6.4mm, Right: 6.3mm)
	Bordered Auto Duplex Printing:	Top margin: 5mm, Bottom margin: 5mm, Left / Right margin: 3.4mm (LTR / LGL: Left: 6.4mm, Right: 6.3mm)
Recommended Printing Area	Top Margin:	40.7mm
	Bottom Margin:	37.4mm
Paper Size	A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", 8 x 10", Envelopes (DL, COM10)	
Paper Handling [Cassette (Upper)] (Maximum Number)	Photo Paper Pro Platinum (PT-101)	4 x 6" = 20
	Photo Paper Plus Glossy II (PP-201)	4 x 6" = 20
	Photo Paper Plus Semi-gloss (SG-201)	4 x 6" = 20
	Glossy Photo Paper "Everyday Use" (GP-501)	4 x 6" = 20

	Matte Photo Paper (MP-101)	4 x 6" = 20
	Photo Stickers (PS-101)	1
Paper Handling [Cassette (Lower)] (Maximum Number)	Plain Paper	A4, A5, B5, LTR, LGL = 125
	High Resolution Paper (HR-101N)	A4 = 65
	Photo Paper Pro Platinum (PT-101)	A4 = 10
	Photo Paper Plus Glossy II (PP-201)	A4 = 10
	Photo Paper Pro Luster (LU-101)	A4 = 10
	Photo Paper Plus Semi-Gloss (SG-201)	A4, 8 x 10" = 10
	Glossy Photo Paper "Everyday Use" (GP-501)	A4 = 10
	Matte Photo Paper (MP-101)	A4 = 10
	T-Shirt Transfer (TR-301)	1
	Envelope	European DL / US Com. #10 = 10
Paper Handling (Disc Tray)	Printable Disc:	1 (Manual handling by disc tray)
Support Media for Auto Duplex Printing	Type:	Plain Paper
	Size:	A4, A5, B5, LTR
Paper Weight	Cassette (Upper):	Canon specialty paper: Max paper weight: Approx. 300g/m ² (Photo Paper Pro Platinum PT-101)
	Cassette (Lower):	Plain Paper: 64-105 g/m ² , Canon specialty paper: max paper weight: approx. 300g/m ² (Photo Paper Pro Platinum PT-101)
Ink End Sensor	Optical sensor + Dot count	
Print Head Alignment	Auto / Manual	
Network		
Protocol	TCP / IP	
Wireless LAN	Network Type:	IEEE802.11n / IEEE802.11g / IEEE802.11b (Infrastructure mode)
	Frequency Band:	2.4GHz
	Data Rate (Standard Value)* ⁴ :	IEEE802.11n: 150Mbps IEEE802.11g: 54Mbps IEEE802.11b: 11Mbps

	Range:	Indoor 50m (depends on the transmission speed and conditions)
	Security:	WEP64 / 128 bits, WPA-PSK (TKIP / AES), WPA2-PSK (TKIP / AES)
System Requirements (Please visit www.canon-asia.com to check OS compatibility and to download the latest driver updates.)	Windows:	Windows XP / Windows Vista / Windows 7
	Macintosh:	Mac OS X v10.5 onwards
General		
Interface	Wireless LAN b/g/n, USB 2.0 Hi-Speed	
Self-Opening Paper Output Tray	Available	
Operating Environment	Temperature:	5 - 35°C
	Humidity:	10 - 90% RH (no dew condensation)
Storage Environment	Temperature:	0 - 40°C
	Humidity:	5 - 95% RH (no dew condensation)
Acoustic Noise (PC Print)	Photo (4 x 6")* ⁵	approx. 44dB(A)
Power	AC 100-240V, 50 / 60Hz	
Power Consumption	Standby:	Approx. 2.1W
	Printing* ⁶ :	Approx. 24W
Environment	Regulation:	RoHS (EU, China), WEEE (EU)
	Eco-Label:	Energy Star
Dimension (W x D x H)	Approx. 451 x 368 x 128mm	
Weight	Approx. 6.6kg	