Imaging Processor	DIGIC 6		
Image Sensor			
Camera Effective Pixels	Approx. 20.2 megapixels (aspect ratio: 3:2)		
Sensor Size	1.0 type		
Lens			
Focal Length	4.2x zoom:	8.8 (W) - 36.8 (T) mm 35mm film equivalent: 24 (W) - 100 (T) mm)	
Focusing Range	5cm (2.0 in.) - infinity (W), 40cm (1.3 ft.) - infinity (T)		
	Macro:	5 - 50cm (W) (2.0 in 1.6 ft. (W))	
Image Stabilizer (IS) System	Lens-shift type		
Electronic Viewfinder			
Effective Pixels	Approx. 2,360,000 dots		
Screen Size	0.39 type		
Coverage	Approx. 100%		
LCD Monitor			
Туре	3.0-inch type, TFT colour LCD with wide viewing angle		
Effective Pixels	Approx. 1,040,000 dots		
Aspect Ratio	3:2		
Features	Touch-screen panel (capacitive type), Vari-Angle		
Focus			
Control System	Autofocus: Continuous, Servo AF Manual Focus		
AF Frame	1-point, Face+Tracking (AF points: up to 31) Touch AF is available		
Metering System	Evaluative, Center-weighted	Evaluative, Center-weighted average, Spot	
ISO Speed (Standard Output Sensitivity, Recommended Exposure Index)	AUTO, ISO 125 – ISO 12800 1/3-stop increments		
Shutter Speed	1 - 1/2000sec. 30 - 1/2000sec. (in Tv Mode) (BULB) - 1/2000sec. (in M Mode)		
Aperture			
Туре	Iris diaphragm		

f/number	f/1.8 - f/11 (W), f/2.8 - f/11 (T)	
Flash		
Modes	Auto, On, Slow Synchro, Off	
Range	50cm – 7.0m (W), 50cm - 4.0m (T) (1.6 – 23ft. (W), 1.6 – 13ft. (T))	
Hotshoe	Available	
Shooting Specifications		
Shooting Modes	High Dynamic Range, Nos Miniature Effect, Toy Cam Defocus, Soft Focus, Mond Effect, Fireworks *2 Standard Movie, Short C Movie	ar* ³ , Handheld NightScene, talgic, Fish-eye Effect,
	Shooting movies is possible with the movie button	
Continuous shooting (AUTO, P Mode)	Approx. 5.9 shots/sec.	
Recording Specifications		
Number of Recording Pixels	Still Images: (4:3)	4:3 Large: 4864 x 3648 Medium 1: 3840 x 2880 Medium 2: 2048 x 1536 Small: 640 x 480
	Still Images: (3:2)	3:2 Large: 5472 x 3648 Medium 1: 4320 x 2880 Medium 2: 2304 x 1536 Small: 720 x 480
	Aspect Ratio:	3:2 / 16:9 / 4:3 / 1:1
	Movies:	1920 x 1080 / 1280 x 720 / 640 x 480
Power Supply	Battery Pack NB-13L	
Number of Shots (CIPA compliant)	Approx. 210 images	

Number of Shots (Eco Mode)	Approx. 320 images	
Movie Recording Time (Actual usage time)	Approx. 40mins.	
Dimensions (CIPA compliant)	112.4 x 76.4 x 44.2 mm (4.43 x 3.01 x 1.74 in.)	
Weight (CIPA compliant)	Approx. 377g (13.3oz.) (including the battery and memory card)	
Other Features	Wi-Fi, NFC, Control Ring, Hot Shoe, USB Charging	
AF modes	One Shot, Servo AF	
AF System Points	1-point, Face+Tracking Touch AF is available	
Built-in Flash Range (Telephoto)	50cm - 4.0m	
Built-in Flash range (Wide Angle)	50cm – 7.0m	
Closest Focus Distance (Telephoto) (cm) (Approximately)	40cm - infinity	
Closest Focus Distance (Wide Angle) (cm) (Approximately)	5cm - infinity	
Continuous Shooting Speed (shots per sec) (Up to)	Approx. 5.9	
Digital Zoom	4x	
Dimensions (mm) (Excl. Protrusions) (Approximately)	112.4 x 76.4 x 44.2	
Effective ISO	ISO 125 - ISO 12800, Auto	
Effective Pixels (Megapixels) (Approximately)	20.2	
Flash Modes	Auto, On, Slow Synchro, Off	
Focal Length (35mm Equivalent)	24 – 100	
Image Size	4:3 Large: 4864 x 3648 Medium 1: 3840 x 2880 Medium 2: 2048 x 1536 Small: 640 x 480 3:2 Large: 5472 x 3648	
	Medium 1: 4320 x 2880 Medium 2: 2304 x 1536 Small: 720 x 480	
Image Stablizer	Yes	

LCDM '(G') (L 1)	2.0	
LCD Monitor (Size) (Inch)	3.0	
LCD Monitor Resolution (dots) (Approximately)	1,040,000	
Manual Focus	Yes	
Memory Card Type	SD / SDHC / SDXC	
Metering System	Evaluative, Center-weighted average, Spot	
Movie Mode (30fps)	1920 x 1080 60p/30p, 1280 x 720 30p, 640 x 480 30p	
Optical Zoom	4.2x	
Optional Power	-	
Peripheral Connections	Hot Shoe	
Processor Type	DIGIC 6	
Shooting Modes (SCN)	Self Portrait, Portrait, Star, Handheld NightScene, High Dynamic Range, Nostalgic, Fish-eye Effect, Miniature Effect, Toy Camera Effect, Background Defocus, Soft Focus, Monochrome, Super Vivid, Poster Effect, Fireworks	
Shooting Modes (Standard)	C, M, Av, Tv, P, Hybrid Auto, Auto, Creative Shot, SCN, Movie	
Shutter Speed Range	(BULB) - 1/2000sec.	
Standard Power Supply	Battery pack NB-13L	
Still Image Format	JPEG, RAW	
Viewfinder Type	Electronic Viewfinder	
Weight (g) (Body) (Approximately)	377	
White Balance Type	Auto, Day Light, Shade, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash, Custom 1, Custom 2	