

# Specifications for imageCLASS LBP151dw

<b>Print</b>		
Printing Method	Monochrome Laser Beam Printing	
Print Speed (A4)	27ppm	
Print Resolution	600 × 600dpi 1200 × 1200dpi equivalent	
First Print Out Time (FPOT)	Approx. 8.0secs.	
Print Language	UFR II LT, PCL 6	
Warm-up Time (from power on)	15secs. or less	
Recovery Time (from sleep mode)	Approx. 1.0sec.	
Auto Duplex Printing	Standard	
Available Paper Size for Auto Duplex Print (60 to 105 g/m <sup>2</sup> )	A4, Letter, Legal <sup>*1</sup> , Indian Legal, Foolscap	
<b>Paper Handling</b>		
Paper Input (based on 64g/m <sup>2</sup> )	Standard Cassette	250 sheets
	Multi-Purpose Tray	1 sheet
	Maximum Paper Capacity	251 sheets
Paper Output (based on 64g/m <sup>2</sup> )	100 sheets	
Paper Size	Standard Cassette	A4, B5, A5, Legal <sup>*1</sup> , Letter, Statement, Executive, Foolscap, 3x5 Index Card, Indian Legal Envelope: COM10, Monarch, C5, DL Custom: width 76.2 - 216.0mm x length 210.0 - 356.0mm
	Multi-Purpose Tray	A4, B5, A5, Legal <sup>*1</sup> , Letter, Statement, Executive, Foolscap, 3x5 Index Card, Indian Legal Envelope: COM10, Monarch, C5, DL Custom: width 76.2 - 216.0mm x length 127.0 - 356.0mm
Paper Weight	Standard Cassette	60 - 163g/m <sup>2</sup>
	Multi-Purpose Tray	60 - 163g/m <sup>2</sup>
Paper type	Plain Paper, Heavy Paper, Bond Paper, Label, Envelope, Index Card	
<b>Connectivity and Software</b>		
Standard Interfaces	Wired	USB2.0 High Speed, 10BASE-T/100BASE-TX
	Wireless	Wi-Fi 802.11b/g/n
Network Security	Wired	IP / Mac address filtering, IEEE802.1x, SNMPv3
	Wireless	WEP, WPA-PSK (TKIP/AES-CCMP), WPA2-PSK (TKIP/AES-CCMP)
Mobile Print	Canon PRINT Business, Mopria® Print Service, Google Cloud Print™, Canon Print Service	

Compatible Operating Systems	Windows® 10 (32/64-bit), Windows® 8.1 (32/64-bit), Windows® 8 (32/64-bit), Windows® 7 (32/64-bit), Windows® Vista (32/64-bit), Windows® Server 2012 R2 (64-bit), Windows® Server 2012 (64-bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2008 (32/64-bit), Windows® Server 2003 R2 (32/64-bit), Windows® Server 2003 (32/64-bit) Mac OS <sup>*2</sup> 10.5.8~, Linux <sup>*2</sup>		
<b>General Specification</b>			
Device Memory	512MB		
Dimensions (W×D×H)	390 x 365 x 245mm		
Weight	Approx. 8.0 kg		
Power Consumption	Maximum	1,120W or less	
	Average (during operation)	260W or less	
	Average (during standby)	2.6W or less	
	Average (during sleep)	Approx. 1.1W or less (USB) Approx. 1.2W or less (wired) Approx. 1.8W or less (wireless)	
Noise Level	During Operation	Sound Pressure Level:	52dB
		Sound Power Level:	66dB
	During Standby	Sound Pressure Level:	Inaudible
		Sound Power Level:	Inaudible
Power Requirement	220 - 240V, 50 / 60Hz		
Operating Environment	Temperature:	10 - 30°C	
	Humidity:	20% to 80% RH (no condensation)	
Toner Cartridge <sup>*3</sup>	Cartridge 337: 2,400 pages (bundled cartridge: 1,700 pages)		
Monthly Duty Cycle <sup>*4</sup>	15,000 pages		
Recommended Monthly Print Volume	500 - 1,500 pages		