

Specifications for imageCLASS LBP7110Cw

| | | |
|---|---|---|
| Print | | |
| Printing Method | Colour Laser Beam Printing | |
| Fixing Method | On Demand Fixing | |
| Print Speed | Mono: | 14ppm (A4 / Letter) |
| | Colour: | 14ppm (A4 / Letter) |
| Print Resolution | 600 x 600dpi | |
| | 9600 (equivalent) x 600dpi | |
| | 1200 x 1200dpi (equivalent) | |
| First Printout Time (FPOT) | 18/18secs. (A4 / Letter) | |
| Warm-up Time (from Power On) | 20secs. or less | |
| Recovery Time (from Deep Sleep) | Approx. 4secs. | |
| Print Language | UFR II LT | |
| Paper Handling | | |
| Paper Input (based on 80g/m ²) | 150 sheets | |
| Paper Output (based on 80g/m ²) | 125 sheets (Face-Down) | |
| Paper Size | A4 / B5 / A5 / Letter / Legal* / Executive / 16K / Foolscap / Statement / Envelope COM-10 / Envelope Monarch / Envelope C5 / Envelope DL / 3 x 5 index card / Custom (Width: 83 ~ 215.9mm x Length: 127.0 ~ 355.6mm) * Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches) | |
| Paper Weight | 60 ~ 220g/m ² | |
| Print Margins | 5mm-top, bottom, left and right (Envelope: 10mm) | |
| Connectivity and Software | | |
| Standard Interfaces | Wired: | USB 2.0 High Speed 10Base-T/100Base-TX |
| | Wireless: | IEEE802.11b/g/n (Infrastructure Mode, WPS Easy Setup) |
| Compatible Operating Systems | Windows: | Windows XP (32bit / 64bit) / Windows Server 2003 (32bit / 64bit) / Windows Vista (32bit / 64bit) / Windows Server 2008 (32bit / 64bit) / Windows Server 2008 R2 (64bit) / Windows 7 (32bit / 64bit) |
| | Macintosh: | Mac OS 10.6 and above* ¹ |
| | Linux | |
| | Citrix | |
| General Specifications | | |
| Operation Panel | 4 Keys, 12 LEDs | |
| Device Memory | 64MB | |
| Noise Level* ³ | During Operation: | 6.52B or less (Sound Power) Approx. 49dB (Sound Pressure) |
| | During Standby: | Inaudible (Sound Power)* ⁴ |

| | | |
|--|--|---|
| | | Inaudible (Sound Pressure)* ⁴ |
| Power Consumption | Maximum: | 800W or less |
| | During Operation: | Approx. 340W |
| | During Standby: | Approx. 10W |
| | During Sleep: | Approx. 0.9W/4W (wireless) |
| Energy Star TEC (Typical Electricity Consumption) | 0.4 kWh/week | |
| Dimensions (Width x Depth x Height) | 406 x 454 x 255mm (Excluding protrusion) | |
| Weight (without Cartridge) | Approx. 16.6kg | |
| Power Requirements | 220-240V (±10%), 50/60Hz (±2Hz) | |
| Operating Environment | Temperature: | 10~30°C |
| | Humidity: | 20~80%RH (No Condensation) |
| Toner Cartridge* ⁵ | Cartridge 331 Black: | 1,400 pages (Bundled Cartridge: 800 pages) |
| | Cartridge 331 II Black: | 2,400 pages |
| | Cartridge 331 CMY: | 1,500 pages (Bundled Cartridge: 800 pages) |
| Monthly Duty Cycle* ⁶ | 30,000 pages | |
| Recommended Monthly Print Volume | 200 - 1,000 pages | |