

# Specifications for imageCLASS LBP841Cdn

<b>Print</b>		
Printing Method	Colour Laser Beam Printing	
Print Speed	A4	26 / 26ppm (mono / colour)
	A3	15 / 15ppm (mono / colour)
Print Resolution	600 × 600dpi 1,200 × 1,200dpi 9,600 (equivalent) × 600dpi	
First Print Out Time (FPOT)	Approx. 7.9 / 9.9secs. (mono / colour)	
Print Language	UFR II PCL6 (45 scalable fonts)	
Warm-up Time (from power on)	29secs. or less	
Recovery Time (from sleep mode)	Approx. 9secs.	
Auto Duplex Printing	Standard	
Available Paper Size for Auto Duplex Print	A3, B4, A4, B5, A5, Legal <sup>*1</sup> , Letter, Executive, Foolscap	
<b>Paper Handling</b>		
Paper Input	Standard Cassette	250 sheets
	Multi-Purpose Tray	100 sheets
	Maximum Paper Capacity	2,000 sheets
Paper Output	250 sheets (face down)	
Paper size	Standard Cassette	A3, B4, A4, B5, A5, Legal <sup>*1</sup> , Letter, Executive, Foolscap Custom: width 148.0 – 297.0mm, length 182.0 – 431.8mm
	Multi-Purpose Tray	A3, B4, A4, B5, A5, Legal <sup>*1</sup> , Letter, Executive, Foolscap, Index Card (3 x 5") Envelope: ISO-C5, No.10, Monarch, DL Custom: width 76.2 – 304.8mm, length 120.0 – 457.2mm
Paper Weight	Standard Cassette	60 – 128g/m <sup>2</sup>
	Multi-Purpose Tray	60 – 220g/m <sup>2</sup>
Paper Type	Plain, Heavy, Label, Envelope	
<b>Connectivity &amp; Software</b>		
Standard Interface	USB 2.0 High Speed 10Base-T / 100Base-TX / 1000Base-T	
Network Interface	Supported protocol: TCP / IP (Frame type: Ethernet II) Print application: LPD, RAW, IPP/IPPS, FTP, WSD	

Mobile Print	Canon PRINT Business, Canon Print Service	
Compatible operating systems	Windows® 10 (32 / 64-bit) Windows® 8.1 (32 / 64-bit) Windows® 8 (32 / 64-bit) Windows® 7 (32 / 64-bit) Windows® Vista (32 / 64-bit) Windows® Server 2012 (64-bit) Windows® Server 2008 R2 (64-bit) Windows® Server 2008 (32 / 64-bit) Windows® Server 2003 (32 / 64-bit) Mac OS <sup>*2</sup> 10.6.8~, Linux <sup>*2</sup>	
<b>General Specifications</b>		
Device Memory	512MB	
Operation Panel	5-line LCD Display	
Dimensions (W x D x H)	545 x 591 x 361.2mm	
Weight	34kg	
Power Consumption	Maximum	1,420W or less
	During Operation	Approx. 530W
	During Standby	Approx. 22.5W
	During Sleep	Approx. 3W (USB connection) Approx. 1.5W (Wired LAN connection)
Noise level <sup>*3</sup>	During Operation	Sound Power: 6.6B or less Sound Pressure: 51dB
	During Standby	Inaudible <sup>*4</sup>
Power Requirement	220 – 240V, 50 / 60Hz	
Operating Environment	Temperature: 10 – 30°C Humidity: 20 – 80% RH (no condensation)	
Toner Cartridge <sup>*5</sup>	Standard	Cartridge 335E Black: 7,000 pages (bundled: 7,000 pages) Cartridge 335E C / M / Y: 7,400 pages (bundled: 7,400 pages)
	High	Cartridge 335 Black: 13,000 pages Cartridge 335 C / M / Y: 16,500 pages
Monthly Duty Cycle <sup>*6</sup>	75,000 pages	
<b>Optional Accessories</b>		
Paper Feeder–E1	Paper Capacity	550 sheets
	Paper Size	A3, B4, A4, B5, A5 <sup>*7</sup> , Legal <sup>*1</sup> , Letter, Executive, Foolscap Custom: width 148.0 – 297.0mm, length 182.0 – 431.8mm
	Paper Weight	60 to 128 g/m <sup>2</sup>