

## Specifications for DR-C240

<b>Type</b>	Desktop sheetfed scanner	
<b>Document Feeding</b>	Automatic or manual sheet feeding	
<b>Document Size</b>	Width:	50.8 - 216mm
	Length:	53.9 - 356mm
	*You can scan documents up to 3,000mm long by setting the scanner to the Long Document mode.	
<b>Document thickness and weight</b>	Automatic Feeding:	0.04 - 0.3mm, 27 - 255g/m <sup>2</sup>
	Manual Feeding:	0.04 - 0.25mm, 27 - 209g/m <sup>2</sup>
<b>Card size and thickness</b>	Size:	54 x 86mm
	Thickness:	1.4mm or less
<b>Passport</b>	4mm or less (include carrier sheet)	
<b>Feeding Capacity</b>	60 sheets (80g/m <sup>2</sup> )	
<b>Scanning Element</b>	CMOS CIS	
<b>Light Source</b>	LED (red, green, and blue)	
<b>Scanning Side</b>	Simplex / Duplex / Skip blank page / Folio	
<b>Scanning Modes</b>	Black and white, Error diffusion, Advanced Text Enhancement II	
	256-level Greyscale	
	24-bit Colour	
<b>Scanning Resolutions</b>	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
<b>Scanning Speed*</b> <b>(A4 / LTR, Portrait, 200dpi)</b>	Black and White	45ppm (simplex) / 90ipm (duplex)
	256-level Grayscale	45ppm (simplex) / 90ipm (duplex)
	24-bit Colour	30ppm (simplex) / 60ipm (duplex)
<b>Useful Functions</b>	Double feed detection, Advanced text enhancement, Skip blank page, Prescan, Auto paper detection, Deskew, Batch separation, Colour drop-out, Colour enhancement, Text orientation recognition, Continuous scanning, Edge enhancement, Preset gamma curve, Scan area settings, Multistream settings, Folio scanning, Remove background, Moire reduction, Background smoothing, Full auto mode.	
<b>Interfaces</b>	Hi-Speed USB 2.0	
<b>Software</b>	ISIS / TWAIN Driver, CaptureOnTouch, CapturePerfect, eCopy PDF Pro Office, Kofax VirtualReScan Basic	
<b>Power Requirements</b>	AC 100 - 240V (50 / 60Hz)	
<b>Power Consumption</b>	Scanning:	19W or less
	Sleep Mode:	1.4W or less
	Power Turned Off:	0.1W or less
<b>Operating Environment</b>	10 - 32.5°C	
	Humidity:	20 - 80% RH
<b>Dimensions (W x D x H)</b>	291 x 253 x 231mm, with feed trays closed	
<b>Weight</b>	Approx. 2.8kg, excluding AC adapter	
<b>Options / Consumables</b>	Flatbed Scanner Unit 101/201, Barcode Module, 2D codw Module, Exchange Roller Kit (feed roller, retard roller, document holding guide), Carrier Sheet (A4).	

Specifications are subject to change without notice.

\*

Actual scanning speed may vary depending on your system configuration and PC