## Specifications for DR-M1060

Туре	Desktop sheetfed sca	nner	
Document size	Plain paper	Width: 50.8mm to 300mm	
		Length: 70mm to 432mm	
		(You can scan documents up to 3,000mm long by	
		setting the scanner to the Long Document mode.)	
	Business card	Width: 50.8mm to 55mm	
		Length: 85mm to 91mm	
	Card	54 x 86mm (ISO standard)	
Document thickness and weight	Plain paper	U-turn path (page separation): 27 to 128g/m² (0.04 mm	
	ram pape.	to 0.15mm)	
		U-turn path (non separation): 27 to 164g/m <sup>2</sup> (0.04 mm to 0.2mm)	
		Straight path: 27 to 255g/m <sup>2</sup> (0.04mm to 0.3mm)	
		128 to 380g/m <sup>2</sup> (0.15mm to 0.45mm)	
	B	(Use the straight path and place vertically.)	
	Business card Card	(Ose the straight path and place vertically.)	
	Card	0.76mm or less, 1.4mm or less for the embossment	
		(Use the straight path and place vertically.)	
Scanning sensor	Contact image sensor		
Light source	LED		
Scanning side	Simplex / Duplex		
Scanning modes	Black and White, Error Diffusion, 256-level Grayscale, Advanced Text		
**	Enhancement, Advanced Text Enhancement II, 24-bit Color		
Scanning Resolutions *1	100 x 100dpi / 150 x 150dpi / 200 x 200dpi / 240 x 240dpi / 300 x 300dpi / 400 x 400dpi / 600 x 600dpi		
Scanning Speed *2			
Grayscale	Simplex:	200dpi: 60ppm	
		300dpi: 60ppm	
	Duplex:	200dpi: 120ipm	
Colour	Cinanlavi	300dpi: 120ipm	
Colour	Simplex:	200dpi: 60ppm	
	Duploys	300dpi: 40ppm 200dpi: 120ipm	
	Duplex:	300dpi: 80ipm	
ADF capacity (80g/m² paper)	A4:	60 sheets	
	A3:	25 sheets	
Interfaces	Hi-Speed USB 2.0		
Other functions	Prescan, Staple detection, Addon, Double feed detection ignore		
Dimensions (W x D x H)	When trays are closed:	424 × 246 × 120mm	
	When trays are opened:	424 × 440 × 210mm	
Weight (without AC adapter)	Approximately 6.1kg		
Power supply (using AC adapter)	DC24V 1.3A		
Power Consumption	Scanning:	32.5W or less	
	In the sleep mode:	2.5W or less	
	p :::= =:=:		
	With power switch	O FW or loss	
	OFF:	0.5W or less	
Noise	· ·	0.5W or less	
Noise Operating environment	OFF:	0.5W or less 10°C to 32.5°C	

Consumables	Exchange Roller Kit	
-------------	---------------------	--

## Specifications are subject to change without notice.

*1	Primary scan lines x secondary scan lines
*2	Conditions: Core i7 2.8 GHz CPU, 4 GB memory, A4 horizontal document size