

Specifications for FAX-L170

Print		
Printing Method	Monochrome Laser	
Print Speed (A4 / Letter)	18 / 19ppm	
Print Resolution	Up to 600 x 600dpi 1200 (equivalent) x 600dpi	
Warm-up Time (From Power On)	14secs. or less	
First Printout Time (FPOT)	Black:	Approx. 7.8secs. (A4), 7.7secs. (LTR)
Recovery Time (From Sleep Mode)	Approx. 3.5secs.	
Print Language / Emulation	UFR II LT	
Print Margins	Top: 5mm, bottom: 6mm, left: 5mm, right: 5mm (Other sizes than Envelope) 10mm - top, bottom, left and right (Envelope)	
Print Features	Watermark, Page composer, Toner saver	
Copy		
Copy Speed	LTR:	12.4cpm (copies per minute)
	A4:	11.8cpm (copies per minute)
Copy Resolution	600 x 600dpi	
First Copy Time (FCOT)	Black:	Approx. 22.3secs. (A4), 21.3secs. (LTR)
Maximum Number of Copies	Up to 99 copies	
Reduce / Enlargement	50 - 200% in 1% increments	
Copy Features	Density adjustment, Toner saver	
Fax		
Modem Speed	Up to 33.6Kbps	
Fax Resolution	Up to 200 x 400dpi	
Compression Modes	MH, MR, MMR	
Memory Capacity* ¹	Up to 512 pages	
One-Touch Dial	30 dials	
Speed Dial (One Touch + Coded dials)	Up to 130 dials	
Group Dials / Destinations	Max. 129 dials / Max. 129 destinations	
Sequential Broadcast	Max. 140 destinations	
Receive Mode	Fax only, Manual, Answering, Fax / Tel Auto switch	
Memory Backup	Yes, 5 minutes	
FAX Features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports	
Paper Handling		
Auto Document Feeder	30 sheets (80g/m ² or less)	
Available Paper Size for ADF	A4, B5, A5, B6, Letter, Legal, Statement Min. 127 x 139.7mm to Max. 216 x 356mm	
Paper Input	Plain Paper (60 - 80g/m ²):	150-sheet cassette
Paper Output	100 sheets (face down)	
Paper Sizes	A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, Postcard, Postcard without folding line, Tetrahedral Postcard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 127mm to Max. 216 x 356mm)	
Paper Types	Plain, Heavy, Recycled, Transparency, Label, Envelope	
Paper Weight	60 to 163g/m ²	
Connectivity and Software		
Standard Interface(s)	USB 2.0 High Speed	
OS Compatibility	Windows 7 (32 / 64 bits* ²), Windows Vista (32 / 64 bits* ²), Windows XP (32 / 64 bits* ²), Windows 2000	

	Mac® OS X 10.4.9 & up* ² , Linux* ³	
Software Included	Printer driver, Fax driver	
General Specification		
CPU	Canon Custom Processor 133MHz	
Memory	64MB (Max.)	
LCD Display	5-line B/W LCD	
Dimensions (W x D x H)	372 x 303 x 303mm (cassette closed) 372 x 400 x 303mm (cassette opened)	
Weight	8.2kg (with cartridge) 8.8kg (without cartridge)	
Power Consumption	Max.:	1020W or less
	During Operation:	Approx. 400W (in copying)
	During Standby:	Approx. 10W
	During Sleep:	Approx. 1.5W
TEC (Typical Electricity Consumption)	0.6 kWh/W	
Noise Levels	Sound pressure level (Bystander's position):	53dB in B/W printing (reference value)
	Sound power level:	6.5B or less in B/W printing
	Sound pressure level (Bystander's position):	Inaudible* ⁴ (reference value)
	Sound power level:	4.3B or less
Operating Environment	Temperature:	50 to 86°F (10 to 30°C)
	Humidity:	20% to 80% RH (no condensation)
Power Requirements	AC 220 to 240V:	50 / 60Hz
Toner Cartridge* ⁵	Cartridge 328:	2,100 pages
	Bundled cartridge:	1,000 pages
Monthly Duty Cycle* ⁶	Up to 8,000 pages	

Specifications are subject to change without notice.

*1	Based on ITU-T #1 Chart (standard mode).
*2	Drivers for Mac OS and Windows 64-bit OS can be downloaded from www.canon-asia.com when available.
*3	Linux supports printing only.
*4	"Inaudible" means each Sound pressure level at bystander's position is less than the absolute criterion value about background noise of ISO 7779.
*5	Toner cartridge yield in accordance with ISO / IEC 19752.
*6	Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.