Specifications for imageCLASS MF232w

PRINT				
Printing Method	Monochrome Laser Bean	n Printing		
Print Speed (A4)	23ppm			
Print Resolution	600 x 600dpi			
Print Quality with Image Refinement	·	·		
Technology				
Warm-Up Time (From Power On)	13.5secs. or less			
First Print Out Time (FPOT) A4	Approx. 6.0secs.			
Recovery Time (From Sleep Mode)	2.0secs. or less			
Print Language	UFR II LT			
Print Margin	5mm-top, bottom, left ar	nd right (Other sizes than Envelope)		
	10mm-top, bottom, left and right (Envelope)			
СОРУ				
Copy Speed (A4)	23ppm			
Copy Resolution	600 x 600dpi			
First Copy Time (FCOT) A4	Approx. 9.0secs.	·		
Maximum Number of Copies	Up to 999 copies			
Reduce / Enlargement	25 - 400% in 1% increments			
Copy Features	Memory Sort, 2 on 1, 4 on 1, ID Card Copy			
SCAN				
Scan Type	Colour Contact Image Sensor			
Scan Resolution	Optical	Up to 600 x 600dpi		
	Driver Enhanced	Up to 9,600 x 9,600dpi		
Maximum Scan Size	Platen Glass	Up to 216 x 297mm		
Scan Speed (*2)	Platen Glass	Approx. 3.0secs. per sheet (mono)		
		Approx. 4.0secs. per sheet (colour)		
Colour Depth	24-bit			
Pull Scan	Yes, USB and Network			
Push Scan (Scan To PC) with MF Scan Utility	Yes, USB and Network			
Scan To Cloud	Voc. MF Coon Hillity			
	Yes, MF Scan Utility			
Scan Driver Compatibility	I WAIN, WIA, ICA	TWAIN, WIA, ICA		
PAPER HANDLING	Standard Cassette	250 sheets		
Paper Input	Multi-Purpose Tray	1 sheet		
Paper Output (Based on 68g/m²)	100 sheets (face down)			
Paper Size	Standard Cassette	A4, B5, A5, Legal, Letter, Statement,		
Paper Size	Standard Casselle	Executive, Government Letter, Government		
		Legal, Foolscap, Indian Legal		
		Custom (Min. 76.2 x 210mm to Max. 216 x		
		356mm)		

	Multi-Purpose Tray	A4, B5, A5, Legal, Letter, Statement,	
		Executive, Government Letter, Government Legal, Foolscap, Indian Legal	
		Custom (Min. 76.2 x 127mm to Max. 216 x 356mm)	
Paper Weight	Standard Cassette	60 to 163g/m ²	
	Multi-Purpose Tray	60 to 163g/m ²	
Paper Type	Plain, Heavy, Recycled, Co	olor, Bond, Label, Index Card, Envelope	
CONNECTIVITY & SOFTWARE			
Standard Interface	Wired	High-Speed USB 2.0	
		10 / 100 Base-T Ethernet	
	Wireless	Wi-Fi 802.11b/g/n (Infrastructure mode, WPS	
		Easy Setup, Direct Connection)	
Network Interface	Print	LPD, RAW, IPP / IPPS, WSD-Print (IPv4, IPv6)	
	Scan	WSD-Scan (IPv4, IPv6)	
	TCP / IP Application	Bonjour(mDNS), DHCP, BOOTP, RARP, Auto IP	
	Services:	(IPv4), DHCPv6 (IPv6)	
	Management	SNMPv1/v3 (IPv4, IPv6), HTTP / HTTPS, SNTP	
Network security	Wired	IP / Mac address filtering, SNMPv3, SSL	
		(HTTPS / IPPS), IEEE802.1x	
	Wireless	WEP 64 / 128-bit, WPA-PSK (TKIP / AES),	
		WPA2-PSK (AES)	
Mobile Printing Capability	Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple AirPrint™, Mopria® Print Service		
Compatible Operating Systems	Microsoft® Windows® 10 (32 / 64-bit), Windows® 8.1 (32 / 64-bit),		
Companione Operating Systems	Windows® 8 (32 / 64-bit), Windows® 7 (32 / 64-bit), Windows Vista® (32 /		
	64-bit), Windows® Server 2012 R2 (64-bit), Windows® Server 2012 (64-		
	bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2008 (32 / 64-bit), Windows® Server 2003 R2 (32 / 64-bit), Windows® Server 2003 (32 /		
	64-bit), Mac OS X ^(*4) 10.6.8~, Linux ^(*3)		
Software Included	Printer driver, Scanner dr	Printer driver, Scanner driver, MF Scan Utility, SSID Tool, Toner Status	
GENERAL			
	256MP		
Device Memory Operational Panel	5-line BW LCD	256MB	
Operational Faller			
Dimensions (W v D v H)	390 v 371 v 312mm /Cass	atta closad)	
Dimensions (W x D x H)	390 x 371 x 312mm (Cass		
	390 x 441 x 312mm (Cass	ette opened)	
Dimensions (W x D x H) Weight	390 x 441 x 312mm (Cass Approx. 10.2kg (without of	ette opened) cartridge)	
Weight	390 x 441 x 312mm (Cass Approx. 10.2kg (without of Approx. 10.8kg (with cart	ette opened) cartridge) ridge)	
	390 x 441 x 312mm (Cass Approx. 10.2kg (without of Approx. 10.8kg (with cart Maximum	ette opened) cartridge) ridge) 1,120W or less	
Weight	390 x 441 x 312mm (Cass Approx. 10.2kg (without of Approx. 10.8kg (with cart	ette opened) cartridge) ridge)	

	During Sleep (Avg.)	Approx. 1.2W (USB connection) Approx. 1.3W (Wired LAN connection) Approx. 2.0W (Wireless LAN connection)	
Noise level ^(*4)	During Operation	Sound Pressure Level: 51.0dB Sound Power Level: 6.6B	
	During Standby	Sound Pressure Level: Inaudible (*5) Sound Power Level: 43dB	
Operating Environment		Temperature: 10 - 30°C Humidity: 20 - 80% RH (no condensation)	
Power Requirement	AC 220 - 240V (±10%),	AC 220 - 240V (±10%), 50 / 60Hz (±2Hz)	
Consumables (*6)	Toner (Standard)	Cartridge 337: 2,400 pages (bundled: 1,700 pages)	
Monthly Duty Cycle (*7)	15,000 pages	15,000 pages	

Specifications are subject to change without notice.

*1	Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches).
*2	Scanning with $300x300$ dpi resolution. The communication time is not included.
*3	<u>Drivers for Mac OS can be downloaded from the here website when available.</u>
*4	Measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296.
* ⁵	"Inaudible" indicates the sound pressure level of each bystander position is below the ISO 7779 absolute criteria for the background noise level.
*6	Declared yield in accordance with ISO / IEC 19752.
* ⁷	Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon laser devices, and does not refer to actual maximum image output per month.