Specifications for imageFORMULA P-208II

Type	Desktop sheet-fed scanner			
Scanning Document Size	Plain Paper:	Width: 50.8 to 216mm		
		Length: 70 to 356mm		
	Postcard:	Width: 88.9 to 108mm		
		Length: 127 to 152.4mm		
	Business Card:	Width: 49 to 55mm		
		Length: 85 to 91mm		
	Card (ISO / IEC Compliant):	54mm x 86mm		
Document Thickness	Plain Paper:	52 to 209g/m^2, Thickness 0.06 to 0.22mm		
	Postcard:	128 to 300g/m^2, Thickness 0.15 to 0.4mm		
	Business Card:	128 to 380g/m^2, Thickness 0.15 to 0.3mm		
	Card (ISO / IEC Compliant):	0.76mm or less		
		Up to 1.4 mm for embossed cards		
Document Feeding Method	Automatic			
Scanning Sensor	Contact image sensor			
Light Source	LED			
Scanning Side	Simplex / Duplex			
Scanning Modes	Black and White, 256-level Grayscale, Advanced Text Enhancement II, 24-bit Colour			
Scanning Resolutions	150 x 150dpi, 200 x 200dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi			
Scanning Speed*[1] *[2]	B&W / Grayscale	Simplex:	200 x 200dpi 8 pages/min.	
			300 x 300dpi 8 pages/min.	
		Duplex:	200 x 200dpi 16 images/min.	
			300 x 300dpi 16 images/min.	
	24-bit Colour	Simplex:	200 x 200dpi 8 pages/min.	
			300 x 300dpi 6 pages/min.	
		Duplex:	200 x 200dpi 16 images/min.	
			300 x 300dpi 12 images/min.	
Interfaces	Hi-Speed USB 2.0			
Scanner driver/ Software	Windows:	ISIS / TWAIN Driver, CaptureOn Touch, CaptureOn Touch Lite (Built-in), Presto! BizCard, Evernote*[3]		
	Mac:	TWAIN Driver, CaptureOn Touch, CaptureOn Touch Lite (Built-in), Presto! BizCard, Evernote*[3]		
Dimensions	Feed tray closed	312.5 x 55.5 x 40mm		
(W x D x H)	Feed tray open	312.5 x 89.5 x 40mm		
Weight	Approx. 600g			
Power Supply	Supply from USB (500 mA)			
Power Consumption	2.5W or less (When connecting with USB cable)			
	1.5W or less (Sleep mode)			
	0.1W or less (Power OFF)			
Operating Environment	Temperature:	10°C to 32.5°C		
	Humidity:	25% to 80% RH		
Options / Consumables	WU10, Carrying Case, Separation Pad			

Specifications are subject to change without notice.

*[1]	Scanning speed may vary depending on PC environment, scanner settings and other factors.

*2	When scanning in duplex made using only USB 2.0 bus power, power consumption on the scanner may fluctuate depending in the type of document being scanned and the processing load on the scammer. In such cases, the scanning speed may vary.
*3	Installed via Internet connection.