

Specifications for imageRUNNER C1325

| | | |
|----------------------------------|--|---|
| Type | Colour Laser Multifunctional (Reader/Printer Separated) | |
| Maximum Original Size | A4 | |
| Acceptable Originals | Sheet, book, and three dimensional objects (up to 2kg) | |
| Paper Sizes | Cassette 1 | A4, B5, A5, and Custom size (98.4 x 190.5mm - 216 x 355.6mm) and Envelopes (COM10 No.10, Monarch, DL, and ISO-C5) |
| | Cassette 2 to 4 | A4, B5, A5, and Custom size (98.4 x 190.5mm - 216 x 355.6mm) |
| | Multi-Purpose Tray | A4, B5, A5, and Custom size (98.4 x 190.5mm - 216 x 355.6mm) and Envelopes (COM10 No.10, Monarch, DL, and ISO-C5) |
| Paper Weight | Paper Drawer | 60 - 163g/m ² |
| | Multi-Purpose Tray | 60 - 220g/m ² |
| Paper Capacity | Cassette 1 | 550 sheets (80g/m ²) |
| | Multi Purpose Tray | 100 sheets (80g/m ²) |
| Resolution | Scan | 300 x 300dpi |
| | Copy | 600 x 600dpi |
| | Print | 600 x 600dpi |
| Copy/Print Speed | Monochrome / Colour: 25 / 25ppm | |
| Magnification | Copy Ratio | 25 - 400% (in 1% increment) |
| First Copy Time | Full Colour: 10.5 seconds Monochrome: 8.4 seconds | |
| Warm-Up Time | From Power On | 34 seconds or less |
| | From Sleep Mode | 10 seconds or less |
| Multiple Copies/Prints | 1 to 999 copies | |
| Memory capacity | 1GB | |
| Interface | Network | Ethernet 10Base-T / 100Base-TX / 1000Base-T (RJ-45) |
| | Others | USB 2.0 x 2 (Host), USB 2.0 (Device), USB 1.1 (Host) |
| Power Supply | 220 - 240V AC, 50/60Hz, 3.7A | |
| Max Power Consumption | Maximum Power Consumption: 1.5 kW or less When the machine is in the Sleep mode*: 1 W When the main power switch is turned OFF: 0.1 W or less * Depending on the system and conditions of use, these values may differ. | |
| Toner Yield (A4, 6% coverage) | Black: 16,500 | |
| | Colour (Cyan, Magenta, Yellow): 11,500 | |
| Drum Yield | Black: 37,900 | |
| | Colour (Cyan, Magenta, Yellow): 23,600 | |
| Dimensions (H x W x D) | 610 x 511 x 549mm | |
| Weight | Approx. 44kg | |
| Installation Space (W x D) | 852 x 564mm (when the multi-purpose tray is extended) | |
| Print Specifications | | |

| | | |
|---|--|---|
| PDL | UFR II (Standard), PCL5c/6 (Optional), Adobe PostScript 3 (Optional) | |
| Resolution | 600 x 600dpi | |
| Supported OS | UFR II | Windows XP, Windows Vista, Windows 7, Windows 8, Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Mac OSX (10.4.9 or later*) *OS X Yosemite is currently not supported at the time of brochure production. |
| | PCL (Optional) | Windows XP, Windows Vista, Windows 7, Windows 8, Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 |
| | Adobe PostScript 3 (Optional) | Windows XP, Windows Vista, Windows 7, Windows 8, Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Mac OSX (10.4.9 or later*) *OS X Yosemite is currently not supported at the time of brochure production |
| Network Protocol | TCP/IP (LPD / Port9100 / WSD / IPP / IPPS / SMB / FTP), IPv6, IPX/SPX (NDS, Bindery), AirPrint | |
| Pull Scan | Network TWAIN Driver (75 - 600 dpi 24bit colour / 8bit grayscale / 2bit Black & White) | |
| Send Specifications | | |
| Scan Speed (A4, 300 dpi) | Black & White / Colour: 51 ipm | |
| Scan Resolution | 300 x 300dpi | |
| Destinations | Email (SMTP), PC Network Folders (SMB, FTP) | |
| Standard File Format | PDF | PDF, Searchable PDF, Compact PDF, Compact & Searchable PDF |
| | Others | TIFF, JPEG |
| Optional File Format (Send PDF Security Feature Set-E1) | PDF | Device Signature PDF, User Signature PDF |
| Automatic Document Feeder | | |
| Size of Originals | A4, B5, A5 and B6 | |
| Original Paper Weights | One-sided originals* | 50 - 105g/m ² |
| | Two-sided originals | 64 - 105g/m ² |
| * When scanning only one sheet of paper, originals from 50 to 128 g/m2 are supported. | | |
| Tray Capacity | 50 sheets (80 g/m ²) | |
| Original Scanning Speed | Copying: 1-sided scanning: 15 sheets/minute (A4 in Black-and-White/Full Colour at 300 x 600 dpi) Scanning: | |

| | |
|--|---|
| | 1-sided scanning: 25 sheets/minute (A4 in Black-and-White/Full Colour at 300 x 300 dpi) |
| Optional Accessories | |
| Cassette Feeding Unit-AJ1 | |
| Paper Sizes | A4, B5, A5, and Custom size 98.4 x 190.5 mm to 216 x 355.6 mm |
| Paper Capacity | 550 sheets (80 g/m ²) x 1 |
| Power Source | From the main unit |
| Power Consumption | Approx. 25W |
| Dimensions (H x W x D) | 425 x 511 x 508mm |
| Weight | Approx 15kg |
| Cassette Feeding Unit-AK1 | |
| Paper Sizes | A4, B5, A5, and Custom size (98.4 x 190.5 - 216 x 355.6mm) |
| Paper Capacity | 550 sheets (8 g/m ²) x 3 |
| Power Source | From the main unit |
| Power Consumption | Approximately 35W |
| Dimensions (H x W x D) | 425 x 511 x 508mm |
| Weight | Approx. 19kg |
| Other Accessories And Supplies | |
| Copy Card Reader-F1, Card Reader Attachment-H1, Super G3 FAX Board, Cassette Heater Unit-39, FL Cassette-AV1, Copy Control Interface Kit-A1, ADF Access Handle-A1, PCL Printer Kit-AZ1, PS Printer Kit-AZ1, Barcode Printing Kit-D1, USB Direct Print (PDF)-K1, NPG-65 Drum Unit K/C/M/Y, NPG-66 Toner K/C/M/Y | |